

# RDAB10-24...

Damper actuator, 10 Nm

Damper actuator for control of dampers in ventilation systems.

- Torque 10 Nm
- For dampers up to approximately 2 m<sup>2</sup>
- Power supply 24 V AC/DC

- On/off or 3-point control signal
- Built-in auxiliary switch RDAB10-24S

RDAB10-24 and RDAB10-24S are damper actuators for control of dampers in ventilation systems.

#### Simple direct mounting

The damper actuator is easily mounted on the damper spindle with the universal spindle clamp. The actuator is supplied with an anti-rotation strap that prevents it from rotating.

#### **Function**

Manual operation is possible with the self-resetting pushbutton (the gearing latch remains disengaged as long as the pushbutton is pressed).

The angle of rotation is adjustable with mechanical end stops.

### Flexible signalisation

RDAB10-24S has a built-in adjustable 0...100% auxiliary switch.

# High functional reliability

The actuator is overload-proof, requires no limit switches and stops automatically when the end stop is reached.



#### Models

RDAB10-24 Basic model

**RDAB10-24S** Model with built-in auxiliary switch

#### Technical data

Supply voltage 24 V AC 50/60 Hz, 24 V DC

Power consumption

In operation (at nominal torque) 1.5 W 0.2 W At rest 3.5 VA For wire sizing

On/off or 3-point Control signal Direction of rotation Selectable with switch

Torque Min. 10 Nm at nominal voltage

Angle of rotation Max. 95°, adjustable 0...100% with mechanical end stops

Running time actuator 150 s

Sound power level Max. 35 dB (A) Mechanical Position indication Protection class **IP54** Ambient temperature -30...+50°C Storage temperature -40...+80°C Cable  $1 \text{ m}, 3 \text{ x} 0.75 \text{ mm}^2$ 


Auxiliary switch (RDAB10-24S) 1 mA ... 3 (0.5) A, 250 V AC


Weight Appr. 850 g

The product conforms with the requirements of European EMC standard C€

89/336/EEC and carries the CE-mark.

# Wiring





Direction of rotation

Auxiliary switch

Connected with conductors S1, S2 and S3 (only model RDAB10-24S)






# **Dimensions**

Damper spindle

Clamp on bottom

Clamp on top



Measurements in mm

**Head Office Sweden** Phone: +46 31 720 02 00

Length O⊥♦

min. 20 10 ... 20

Web: www.regin.se info@regin.se Mail:

Sales Offices

France: +33 14 171 46 46 Hong Kong: +852 24 07 02 81 +65 67 47 82 33 Singapore: Germany: +49 30 77 99 40

