

# RDAB20-24...

Damper actuator, 20 Nm

Damper actuator for control of dampers in ventilation systems.

- Torque 20 Nm
- For dampers up to approximately 4 m<sup>2</sup>
- Power supply 24 V AC/DC

- On/off or 3-point control signal
- Built-in auxiliary switch RDAB20-24S

RDAB20-24 and RDAB20-24S are damper actuators for control of dampers in ventilation systems.

#### Simple direct mounting

The damper actuator is easily mounted on the damper spindle with the universal spindle clamp. The actuator is supplied with an anti-rotation strap that prevents it from rotating.

#### **Function**

Manual operation is possible with the self-resetting pushbutton (the gearing latch remains disengaged as long as the pushbutton is pressed).

The angle of rotation is adjustable with mechanical end stops.

#### Flexible signalisation

RDAB20-24S has a built-in adjustable 0...100% auxiliary switch.

## High functional reliability

The actuator is overload-proof, requires no limit switches and stops automatically when the end stop is reached.



## Models

RDAB20-24 Basic model

RDAB20-24S Model with built-in auxiliary switch

## Technical data

Supply voltage 24 V AC 50/60 Hz, 24 V DC

Power consumption

In operation (at nominal torque) 2 W
At rest 0.2 W
For wire sizing 4 VA

Control signal On/off or 3-point
Direction of rotation Selectable with switch

Torque Min. 20 Nm at nominal voltage

Angle of rotation Max. 95°, adjustable 0...100% with mechanical end stops

Running time actuator 150 s

Sound power level Max. 35 dB (A)
Position indication Mechanical
Protection class IP54
Ambient temperature -30...+50°C
Storage temperature -40...+80°C
Cable 1 m, 3 x 0.75 mm²

Auxiliary switch (RDAB20-24S) 1 mA ... 3 (0.5) A, 250 V AC

Weight Appr. 1050 g


Direction of rotation


(only model RDAB20-24S)

The product conforms with the requirements of European EMC standard

89/336/EEC and carries the CE-mark.

# Wiring






Auxiliary switch Connected with conductors S1, S2 and S3



#### **Dimensions**



 Damper spindle
 Length
 ○ ▼

 Clamp on top
 min. 42
 10 ... 20 (26.7)

 Clamp on bottom
 min. 20
 10 ... 20

Measurements in mm.

#### **Head Office Sweden**

Phone: +46 31 720 02 00 Web: www.regin.se Mail: info@regin.se Sales Offices

France: +33 14 171 46 46 Hong Kong: +852 24 07 02 81 Singapore: +65 67 47 82 33 Germany: +49 30 77 99 40

