

- Torque 5 Nm
- For dampers up to approximately 1 m²
- Power supply 24 V AC/DC

RDAB5-24 and RDAB5-24S are damper actuators for control of dampers in ventilation systems.

Simple direct mounting

The damper actuator is easily mounted on the damper spindle with the universal spindle clamp. The actuator is supplied with an anti-rotation strap that prevents it from rotating.

RDAB5-24...

Damper actuator, 5 Nm

Damper actuator for control of dampers in ventilation systems.

- On/off or 3-point control signal
- Built-in auxiliary switch RDAB5-24S

Function

Manual operation is possible with the self-resetting pushbutton (the gearing latch remains disengaged as long as the pushbutton is pressed).

The angle of rotation is adjustable with mechanical end stops.

Flexible signalisation

RDAB5-24S has a built-in adjustable 0...100% auxiliary switch.

High functional reliability

The actuator is overload-proof, requires no limit switches and stops automatically when the end stop is reached.



Models

RDAB5-24 Basic model

RDAB5-24S Model with built-in auxiliary switch

Technical data

Supply voltage 24 V AC 50/60 Hz, 24 V DC

Power consumption

In operation (at nominal torque) 1 W At rest 0.2 W For wire sizing 2 VA

On/off or 3-point Control signal Direction of rotation Selectable with switch Torque Min. 5 Nm at nominal voltage

Max. 95°, adjustable 0...100% with mechanical end stops Angle of rotation

Running time actuator 150 s

Sound power level Max. 35 dB (A) Mechanical Position indication Protection class **IP54** Ambient temperature -30...+50°C Storage temperature -40...+80°C Cable

Direction of rotation


 $1 \text{ m}, 3 \text{ x} 0.75 \text{ mm}^2$ Auxiliary switch (RDAB5-24S) 1 mA ... 3 (0.5) A, 250 V AC

Weight 600 g

The product conforms with the requirements of European EMC standard CE

89/336/EEC and carries the CE-mark.


Wiring



Auxiliary switch Connected with conductors S1, S2 and S3 (only model RDAB5-24S)



Dimensions



Length O±♦ Damper spindle min. 37 6 ... 20

Measurements in mm

Head Office Sweden Phone: +46 31 720 02 00

Web: www.regin.se info@regin.se Mail:

Sales Offices

France: +33 14 171 46 46 Hong Kong: +852 24 07 02 81 +65 67 47 82 33 Singapore: Germany: +49 30 77 99 40



S1 S2 S3

0...100%